



BLUE RIBBON CORP.

2770 Long Road, Grand Island, NY 14072 USA
 Tel. (716) 773-9300 • Fax (716) 773-5019
 brsales@blueribboncorp.com • www.blueribboncorp.com

BACK CONNECTED UTILITY GAUGES MODEL BR102D

- An inexpensive utility gauge for the broad commercial market.
- Suitable for air, water, oil, gas or any other media not corrosive to brass.
- Other connection locations, mounting styles and accessories available.
- Ready for immediate shipment upon request.

SPECIFICATIONS:

- Available Dial Sizes: 1½", 2", 2½", 4"
- Available Connection Sizes:
 1/8"(M) NPT on 1½" and 2"
 1/4"(M) NPT on 2" thru 4"
- Black Steel Case
- Brass Socket and Movement
- Phosphor Bronze Bourdon Tube
- Dry, Non-Fillable
- Accuracy: 3-2-3%
- Ambient Temperature: -50°F to 160°F
- Dual Scale: PSI & BAR (x100=kPa)



RANGE	CODE	MAJOR INC.	MINOR INC.
30/0" VAC	A	5" hg	.5" hg
30/0/15	CB	10"hg / 5 psi	1"hg / .5 psi
30/0/30	CC	10"hg / 10 psi	1"hg / 1 psi
30/0/60	CD	10"hg / 10 psi	2"hg / 1 psi
30/0/100	CE	30"hg / 20 psi	5"hg / 2 psi
30/0/150	CF	30"hg / 20 psi	5"hg / 2 psi
30/0/300	CH	30"hg / 50 psi	10"hg / 5 psi
0/15	B	2 PSI	.2 PSI
0/30	C	5 PSI	.5 PSI
0/60	D	10 PSI	1 PSI
0/100	E	20 PSI	2 PSI
0/160	F	20 PSI	2 PSI
0/200	G	40 PSI	5 PSI
0/300	H	50 PSI	5 PSI
0/400	I	50 PSI	5 PSI
0/600	K	100 PSI	10 PSI
0/1000	M	200 PSI	20 PSI
0/1500	N	200 PSI	20 PSI
0/2000	O	400 PSI	50 PSI
0/3000	P	500 PSI	50 PSI
0/5000	R	1000 PSI	100 PSI
0/6000	S	1000 PSI	100 PSI
0/10,000	U	2000 PSI	200 PSI

		A	B	C	D	E
1½" DIAL	In.	1.57"	1.04"	.56"	1.57"	1/8" or 1/4 (M)NPT
	MM	40	26	14	40	
2" DIAL	In.	2.07"	1.14"	.83"	1.83"	1/4 (M)NPT
	MM	53	29	21	47	
2½" DIAL	In.	2.50"	1.17"	.86"	2.03"	1/4 (M)NPT
	MM	63	30	22	52	

Blue Ribbon reserves the right to make product improvements and amendments to the product specifications stated throughout this brochure without prior notification. Please contact the factory on all critical dimensions and specifications for verification.