



BLUE RIBBON CORP.

2770 Long Road, Grand Island, NY 14072 USA
Tel. (716) 773-9300 • Fax (716) 773-5019
brsales@blueribboncorp.com • www.blueribboncorp.com

HIGH STATIC PRESSURE DIFFERENTIAL GAUGES

High static pressure that gives a reading in low differential pressure range.

APPLICATIONS:

Filtration and gas systems are the most popular. Also can be used for leak detection.

Please call sales desk at 1-877-774-4751 for specifics and part numbers.

SPECIFICATIONS:

PISTON GAUGE

- Dial: 2.5" and 4"
- Case: SS or Flanged
- Lens: Glass
- Line Connection Locations: In Line (Standard)
Back and bottom on request.
- Connection: 1/4", 1/2", 3/8" NPT, BSP, BSPT
- Wetted Parts: PTFE, SS, ceramic magnet
- Body Material: 316 SS, Aluminum, Brass, Monel
- Internals Movement: Magnetic Coupling, Using
Piston & Spring
- Pointer: Magnetic
- Seal: Buna-N Standard, Viton
- Ranges: 5-150 PSI
- Maximum Pressure: Aluminum 3000 PSI,
316 SS,
6000 PSI
- Maximum Temperature: 175° F (80° C)
- Accuracy: 2% Full scale

