




BLUE RIBBON CORP.

2770 Long Road, Grand Island, NY 14072 USA
Tel. (716) 773-9300 • Fax (716) 773-5019
brsales@blueribboncorp.com • www.blueribboncorp.com

PUMP CONTROLLER BULLDOG BD100 SETPOINT

STANDARD FEATURES:

- Control ON-OFF for two pumps
- Front-panel programming
- Analog output for run times
- Secure menu for all other pre-set values
- 24 VDC power for sensor
- Accepts 4-20 mA or 1-5 VDC
- Non-volatile memory, no batteries
- Alternation of pumps set as default
- Setpoints continuously displayed, along with current level readings



The Bulldog is a setpoint controller designed primarily to accept the 4-20mA output signal from the Birdcage level sensor, turn pumps on and off, and control alarm outputs.

This controller is simple and inexpensive. It is so simple that even the least-trained operator can program six standard level setpoints for the control of the pumps - the on/off setpoints for the two pumps and the settings for the two alarms. That's it! Everything else is defaulted to a secure menu, pre-programmed for the customer. Everything is readily available in case you have to change range or decimal placement, suppress the zero, or turn off the alternation, etc.

The flexibility and variety of options in the secure menu will be applauded by engineers, while the operators will never have to learn those programming steps. Nothing could be easier!

See reverse side for technical specifications and ordering guide.


Blue Ribbon reserves the right to make product improvements and amendments to the product specifications stated throughout this brochure without prior notification. Please contact the factory on all critical dimensions and specifications for verification.



BLUE RIBBON CORP.

2770 Long Road, Grand Island, NY 14072 USA
Tel. (716) 773-9300 • Fax (716) 773-5019
brsales@blueribboncorp.com • www.blueribboncorp.com

Standard Specifications listed below. Consult factory for further options, which may change the overall dimensions.

| | |
|--------------------------------------|---|
| Setpoint Range | Low and High points are selected independently |
| Display | Two 4 digit, 7 segment, 14.2mm (0.56") high LED's |
| Control Action | Selectable for Reverse (pump up) or Direct (pump down); Selectable for alternation or not |
| Control Output Ratings | Relays: 2 each SPDT, 10A at 240 VAC resistive, 1/2 hp at 120 VAC, 1/3 hp at 240 VAC Alarm Relays: 2 each SPST 3A at 240 VAC resistive, 1.5A at 240 VAC inductive, pilot duty rating: 240 VA 2A at 120 VAC or 1A at 240 VAC |
| Additional Outputs | Two switched voltage outputs mirror action of relays, for recording motor start cycles and run times |
| Accuracy | ± 0.25% of reading ±1 least significant digit |
| Resolution | 1 count or 0.1 counts (sensor dependent) |
| Isolation | Relays and SSR outputs, 1500 VAC from all inputs and outputs; 24 VDC loop power, 500 VAC to all inputs and outputs |
| Power Consumption | 5 VA maximum |
| Electrical Supply | 100 to 240 VAC nominal, +10% to 15%, 50 to 400 Hz single phase; 132 to 240 VDC +10% to 20% |
| Loop Powered Supply | Isolated +24 VDC supplies power to the Birdcage or Pressure Sensor |
| Temperature Range | Operating Range: -10°C to +55°C (-14°F to +130°F) Storage Range: -40°C to +80°C (-40°F to +175°F) |
| Agency Approvals | UL508, CE  |
| Humidity Range | 0 to 90% up to 40°C for non-condensing |
| Memory Backup | Non-volatile memory, no batteries |
| Panel Cutout | 92mm X 92mm (3.625" X 3.625") |
| Depth Behind Mounting Surface | 103mm (4.0") |
| Weight | 454 g (16 oz) |
| Front Panel Rating | IP66 (Type NEMA 4X) |

Ordering Guide:

Example: BD100

Part No.