



BLUE RIBBON CORP.

2770 Long Road, Grand Island, NY 14072 USA
Tel. (716) 773-9300 • Fax (716) 773-5019
brsales@blueribboncorp.com • www.blueribboncorp.com

PUMP CONTROLLER BULLDOG BD200 SETPOINT

Dual setpoint controller that is easy to program. Controls submersible pumps in lift stations, and is designed to field calibrate the Birdcage Level Sensor.

STANDARD FEATURES:

- Selectable pump alternation when used with two pumps to minimize pump wear. With alternation "On", a seal failure or over-temperature condition will force the non-failed pump to lead status and stop alternation.
- Alarm light for seal failure when used with a submersible pump that includes a moisture sensor.
- Alarm light for overheating when used with a pump that includes a thermostat. Pump is removed from service & can be brought back online manually or automatically when pump has cooled down.
- Runtime displayed by a front panel button.
- 24 VDC power for level transmitter
- 4-20 mA or voltage signal
- Non-volatile memory, no batteries
- Test System function that simulates the process input to test programming or to insure the pumps are operating.
- User-selectable security lock-out of programming and/or setpoints.



The **Bulldog BD200 Pump Controller** provides versatile level control in a standard 1/4 DIN package.

This controller is versatile, simple, and inexpensive making it the ideal instrument for controlling dual pump lifting stations. Setpoints for ON/OFF and HI/LO alarms are easily set on the front panel. These same buttons also Enable/Disable pump alternation. Selectable time delay up to 60 seconds on power up for pump two prevents both pumps from starting at the same time and a large current draw. Alarms for pump seal failure and motor windings overheating are indicated by lights on the front panel. The dial can also display a runtime clock for each pump. An isolated 4-20 mA retransmission is standard. The front face is rated NEMA-4X for outdoor panel mounting. The BD-200 is also available with RS-232 or RS-485 protocol for connectivity with SCADA systems.

See reverse side for technical specifications and ordering guide.


Blue Ribbon reserves the right to make product improvements and amendments to the product specifications stated throughout this brochure without prior notification. Please contact the factory on all critical dimensions and specifications for verification.



BLUE RIBBON CORP.

2770 Long Road, Grand Island, NY 14072 USA
Tel. (716) 773-9300 • Fax (716) 773-5019
brsales@blueribboncorp.com • www.blueribboncorp.com

Standard Specifications listed below. Consult factory for further options, which may change the overall dimensions.

Inputs	4 (or 0) to 20 mADC or 2 (or 0) to 10 VDC selectable
Input Impedance	Current = 10 ohms, Voltage = 100 K ohms
Output Ratings	Control Relays: SPDT, 10A @ 240 VAC resistive, 1/4 hp @ 120 VAC, 1/3 hp @ 240 VAC Alarm Relays: SPST, 3A @ 240 VAC resistive, 1/10 hp @ 120 VAC
Control Type	On/Off, reverse (pump out) or direct (pump in) acting
Accuracy	± 0.25% of span ± 1 least significant digit
Display	Two 4 digit, 7 segment, 14.2mm (0.56") high LED's
Resolution	1 count
Power Consumption	7.5 VA maximum
Electrical Supply	100 to 240 VAC nominal, +10% to 15%, 50 to 400 Hz single phase; 132 to 240 VDC +10% to 15%
Loop Powered Supply	Isolated +24 VDC @ 50mA, regulated
Temperature Range	Operating Range: -10°C to +55°C (-14°F to +130°F) Storage Range: -40°C to +80°C (-40°F to +175°F)
Humidity Range	0 to 90% up to 40°C for non-condensing
Seal Failure (Moisture Sensor)	Power: 2.5 VDC Search Current: 3 micro amps Resolution: 10K to 500K ohms in 10K ohm steps
Agency Approvals	UL508, CE 
Memory Backup	Non-volatile memory, no batteries
Panel Cutout	92mm X 92mm (3.622" X 3.622")
Weight	454 g (16 oz)
Front Panel Rating	IP66 (Type NEMA 4X)
Options	RS-232 or RS-485 with Mod bus protocol; Ethernet using TCP/IP
Accessories	Weatherproof Enclosures, NEMA 4X

Ordering Guide:

Example: BD200

Part No.